Bass D.I Put up center front mic for SET II but will need only Stage Left & Stage Right mics during 1ST SET; We will sound check all 3 front vocal mics, Rubb StraightStand-ShureBeta58 GooseneckStraightStand-Beta58 Drum kit mics-Snare,1RackTom,1FloorTom,Cymbal overheads D Outlet Mon mix 1 ወ StraightStand-ShureBeta58 Sou D.I. for acoustic DΙ Mon mix 2 D 4 Outlet TriggeredBassDrum D.I. Mon mix 5 ഗ a StraightStand-ShureBeta58 g Outlet BoomStand-Beta58 Left &Right XLR inputs to keys mixer 7 ወ Mon mix 3 Ž. PercussMic(for cowbell by keys) D.I. for acoustic Plot Mon mix 4

Rubber Soul, The Tribute

TECHNICAL RIDER

THIS RIDER IS ATTACHED TO PURCHASE/PERFORMANCE CONTRACT

3) INPUT LIST & STAGE NEEDS (**SEE STAGE PLOT)

Minimum Specifications: (Contact Road Mgr: Dave Gores to approve substitutions)

INPUTS		MIC	STAND	TO MON MIX
1	Kick	SM 91	T-Floor	1, 5
2	Snare	SM 57	T-Boom	
3	Rack Tom	SM 98	Clip	
4	Floor Tom	SM 98	Clip	
5	OverHead Boom1	SM 98	T-Boom	
6	OverHead Boom2	SM 98	T-Boom	
7	Keys (Left Input)	XLR to Keysmixer	Pan Left	All
8	Keys (Right Input)	XLR to Keysmixer	Pan Right	All
9	Keys percuss mic	SM 57	T-Boom	
10	Bass	DI or SM 57	T-Floor	1, 5
11	(Left) Elec Guitar	SM 57	T-Floor	2, 4
12	(Right) Elec Guitar	SM 57	T-Floor	3
13	(Left)Acous Guitar	DI		2,4,5
14	(Right) Acous Guitar	DI		1,3,5
15	(Left-Bass) Vocal	Beta 58	Straight	All
16	(Ctr-Guitar) Vocal	Beta 58	Straight	All
17	(Right-Guitar) Vocal	Beta 58	Straight	All
18	Drum Vocal	Beta 58	Straight (w/gooseneck)	All
19	Keys Vocal	Beta 58	T-Boom	All

NOTES: *If Beta 58 mics not available, use SM 58

**PERFORMANCE ITEMS:

*3 front mics for sound check---Pull down middle mic & stand for 1^{st} set, then put back up for 2^{nd} & 3^{rd} sets

STAGE NEEDS:

- 4 Junction boxes for onstage power-minimum 2 separate circuits (See stage plot for placement)
- 3 small fans for performers
- Please leave a clean stage with cords and cables hidden as much as possible

Road Manager: Dave Gores 1-651-260-9581

Email: dmgores@comcast.net

Website: www.rubbersoulthetribute.com

^{*}For straight stands: Prefer straight with round base;(Alternative--set up T-booms as straight stands)

^{*}Bass can be mic'd if able to provide amp/cabinet in backline; If not and is run through DI, will need 6th monitor to be dedicated Bass mix